



# Krystol Waterstop Treatment™

(Waterproofing System for Construction Joints)

Product Code: K-321

## DESCRIPTION

Krystol Waterstop Treatment is a primary component of the Krystol® Waterstop System and is used to permanently waterproof concrete construction joints. Krystol Waterstop Treatment is specially formulated with Kryton's proven Krystol technology. The active ingredients in Krystol Waterstop Treatment combine chemically with water and concrete to form millions of needle-shaped crystals that grow in all directions to fill any capillary pores, cracks and joints that might otherwise allow water to pass. Krystol Waterstop Treatment is used in conjunction with Krystol Waterstop Grout™ to form the complete system.

## FEATURES

- Provides a permanent waterstop treatment as part of the Krystol Waterstop System
- High-strength and durable, making jobsite damage unlikely
- Safe for contact with potable water, certified by NSF to NSF/ANSI Standard 61 Drinking Water System Components – Health Effects
- Easy to install and distinctive gold color makes it easy to inspect

## KEY BENEFITS

- Easily inspected
- Helps to streamline the construction process by increasing jobsite productivity
- Increases reliability and quality control
- Flexible scheduling – resistant to rain and foot traffic once hardened. Concrete can be placed days or weeks later.

## RECOMMENDED USES

Use in conjunction with Krystol Waterstop Grout as part of the Krystol Waterstop System at all static concrete-to-concrete joints where there is any concern regarding water penetration. May be used in some circumstances as a dampproofing treatment on joints not subject to hydrostatic pressure—Consult a Kryton representative for details.

## PHYSICAL PROPERTIES

Appearance	Buff/yellow powder
Bulk density g/cm <sup>3</sup> (lb. /cu. ft.)	1.2 (75)
pH (when mixed with water)	13

## PLASTIC PROPERTIES

Working time (20°C/ 68°F, 50% RH)	35 minutes
Hardening time (20°C/ 68°F, 50% RH)	5 hours



### APPLICATION

**Read and distribute Application Instructions 4.11 to 4.22 — Use of Krystol Waterstop System (as applicable) before using this product.** Consult a Kryton Representative for help with selecting the appropriate joint detail. Mix Krystol Waterstop Treatment to a thick slurry consistency (approximately 3 parts powder to 1 part clean water by volume), and apply Treatment at construction joints prior to pouring next subsequent concrete. Protect the Treatment application from damage by rain, rapid drying or freezing for at least 24 hours.

### LIMITATIONS

Krystol Waterstop Treatment is effective for rigid structures only and may not reliably seal joints that experience variable loading or repeated movement. Consult a Kryton representative for project specific recommendations.

### SAFETY

Read the Material Safety Data Sheet (MSDS) for this product. For professional use only. This product becomes caustic when mixed with water or perspiration. Avoid contact with skin or eyes. Avoid breathing dust. Wear long sleeves, safety goggles and impervious gloves.

### PACKAGING

- 5 kg (11 lb.) resealable pails
- 25 kg (55 lb.) resealable pails

### SHELF LIFE

Krystol Waterstop Treatment has a minimum shelf life of 24 months for unopened pails, and 4 months for properly resealed pails.

### WARRANTY

Kryton International Inc. warrants that its products are free from manufacturer's defects and, when applied in accordance with the current specification and application instructions will perform as so stated in its product literature. Because methods and conditions of use are beyond the control of Kryton, no guarantee, expressed or implied can be given as to the results of application. Liability of Kryton shall be limited to replacement of materials proved defective or, at its option, refund of the purchase price of the product.