



KRYTON INTERNATIONAL INC. 1645 EAST KENT AVE. VANCOUVER, BC V5P 2S8 TOLL FREE: 1-800-267-8280 PHONE: (604) 324-8280

FAX: (604) 324-8280 www.kryton.com





NEGATIVE SIDE LEAK REPAIR

POSITIVE SIDE LEAK REPAIR

LEAKING CRACK REPAIR

MANUFACTURER'S NOTES:

CHISEL TO CREATE A CHASE ALONG THE ENTIRE LENGTH OF THE LEAKING CRACK OR JOINT TO THE REQUIRED 25 MM X 40 MM (1" X 1.5")

- 1. APPLY KRYSTOL PLUG TO PREPARED CHASE TO STOP FLOWING WATER.
- 2. TIGHTLY PACK REMAINING CHASE WITH KRYSTOL REPAIR GROUT AT A RATE OF APPROXIMATELY 1.6 KG PER LINEAL METER (1 LB. PER LINEAL FOOT).
- 3. WATERPROOF ENTIRE WALL OR SLAB WITH KRYSTOL T1 AT A RATE OF 1.2 KG/M2

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5104-033



5104-033 REVISION DATE 18/12/2018